

# Configuration File Changes

Sitecore Experience Platform 8.0 Update-1



**sitecore**<sup>®</sup>  
Own the experience<sup>™</sup>

## 1.1 Config file changes in Sitecore 8.0 rev. 150121 (Update-1)

There are changes to the configuration file in Sitecore 8.0 rev. 150121 compared to Sitecore 8.0 rev. 141212. When you upgrade an existing solution, you must manually implement the configuration file changes described in this document. This update requires you to make changes to the following files:

- Web.config
- App\_Config\Include\Sitecore.ExperienceEditor.Speak.Requests.config
- App\_Config\Include\Sitecore.ExperienceExplorer.config
- App\_Config\Include\Sitecore.PathAnalyzer.config
- App\_Config\Include\Sitecore.PathAnalyzer.RemoteClient.config.disabled
- App\_Config\Include\Sitecore.PathAnalyzer.Services.RemoteServer.config.disabled
- App\_Config\Include\Sitecore.Speak.config
- App\_Config\Include\SwitchMasterToWeb.config.example
- App\_Config\Include\ContentTesting\Sitecore.ContentTesting.config
- App\_Config\Include\FXM\Sitecore.FXM.config
- App\_Config\Include>ListManager\Sitecore.ListManagement.config
- App\_Config\Include\Social\Sitecore.Social.config
- App\_Config\Include\XdbCloud\Sitecore.Cloud.Xdb.config.disabled

Depending on the search provider, you should also update the following files:

- Sitecore solution configured to use Lucene:
  - App\_Config\Include\FXM\Sitecore.FXM.Lucene.Index.DomainsSearch.config
- Sitecore solution configured to use Solr:
  - App\_Config\Include\Sitecore.ContentSearch.Solr.DefaultIndexConfiguration.config.example
  - App\_Config\Include\FXM\Sitecore.FXM.Solr.Index.DomainsSearch.config.disabled

The clean configuration files for Sitecore 8.0 rev. 150121 (Update-1) can be downloaded using the following links:

- Web.config\_80rev150121.zip
- app\_config\_files\_80rev150121.zip

### 1.1.1 Changes to Web.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `web.config` file:

1. In the `<scheduling>` section, remove the following agents:

```
<!-- Agent to process schedules embedded as items in a database -->
<agent type="Sitecore.Tasks.DatabaseAgent" method="Run" interval="00:10:00">
  <param desc="database">core</param>
  <param desc="schedule root">/sitecore/system/tasks/schedules</param>
  <LogActivity>true</LogActivity>
</agent>
<!-- Agent to process schedules embedded as items in a database -->
<agent type="Sitecore.Tasks.DatabaseAgent" method="Run" interval="00:10:00">
  <param desc="database">master</param>
  <param desc="schedule root">/sitecore/system/tasks/schedules</param>
  <LogActivity>true</LogActivity>
</agent>
```

# Configuration File Changes

## 1.1.2 Changes to `App_Config\Include\Sitecore.ContentSearch.Solr.DefaultIndexConfiguration.config`

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `App_Config\Include\Sitecore.ContentSearch.Solr.DefaultIndexConfiguration.config` file:

### Note

Apply the following changes only if the `App_Config\Include\Sitecore.ContentSearch.Solr.DefaultIndexConfiguration.config.example` file is enabled on your instance.

1. In the `<defaultSolrIndexConfiguration>` section, add the following element to the end of the `<virtualFieldProcessors>` section:

```
<virtualFieldProcessor fieldName="_fullpath"
type="Sitecore.ContentSearch.VirtualFields.FullPathFieldProcessor, Sitecore.ContentSearch" />
```

2. In the `<defaultSolrIndexConfiguration>/<indexFieldStorageValueFormatter>` section, replace the `<converter handlesType="Sitecore.ContentSearch.SitecoreItemUniqueId, Sitecore.ContentSearch"...</converter>` converter with the following one:

```
<converter handlesType="Sitecore.ContentSearch.SitecoreItemUniqueId,
Sitecore.ContentSearch"
typeConverter="Sitecore.ContentSearch.SolrProvider.Converters.SolrIndexFieldSitecoreItemUnique
IDValueConverter, Sitecore.ContentSearch.SolrProvider">
  <param
type="Sitecore.ContentSearch.Converters.IndexFieldItemUriValueConverter,
Sitecore.ContentSearch"/>
</converter>
```

## 1.1.3 Changes to `App_Config\Include\Sitecore.ExperienceEditor.Speak.Requests.config`

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.ExperienceEditor.Speak.Requests.config` file:

- In the `<sitecore.experienceeditor.speak.requests>` section, add the following request after the `ExperienceEditor.Item.HasPresentation` request:

```
<request name="ExperienceEditor.Item.GetUri"
type="Sitecore.ExperienceEditor.Speak.Ribbon.Requests.Common.GetItemUri,
Sitecore.ExperienceEditor.Speak.Ribbon" />
```

## 1.1.4 Changes to `App_Config\Include\Sitecore.ExperienceExplorer.config`

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.ExperienceExplorer.config` file:

1. In the `<processItem>` pipeline, add the following processor between the `<processor type="Sitecore.ExperienceExplorer.Business.Pipelines.ProcessItem.InteractionValuePipeline,...></processor>` and `<processor type="Sitecore.ExperienceExplorer.Business.Pipelines.ProcessItem.ProfilesPipeline,...></processor>` processors:

```
<processor
type="Sitecore.ExperienceExplorer.Business.Pipelines.ProcessItem.SaveInitialProfilesPipeline,
Sitecore.ExperienceExplorer.Business"

patch:before="processor[@type='Sitecore.Analytics.Pipelines.ProcessItem.ProcessProfiles,
Sitecore.Analytics']"></processor>
```

2. Add the following processor to the end of the `<httpRequestEnd>` pipeline:

```
<processor
type="Sitecore.ExperienceExplorer.Business.Pipelines.HttpRequestProcessed.SetModeChangedMarker,
Sitecore.ExperienceExplorer.Business"></processor>
```

## 1.1.5 Changes to App\_Config\Include\Sitecore.PathAnalyzer.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.PathAnalyzer.config` file:

1. In the `<pathAnalyzer>` section, replace the `<mapRepository>` element with the following one:

```
<mapRepository type="Sitecore.PathAnalyzer.Data.MapItemRepository,
Sitecore.PathAnalyzer" />
```

## 1.1.6 Changes to App\_Config\Include\Sitecore.PathAnalyzer.RemoteClient.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.PathAnalyzer.RemoteClient.config` file:

### Note

Apply the following changes only if the `App_Config\Include\Sitecore.PathAnalyzer.RemoteClient.config.disabled` file is enabled on your instance.

1. In the `<settings>` section, add the following settings:

```
<!-- PATH ANALYZER - REMOTE SERVICES - AUTHENTICATION - API KEY
Specifies the key to use for HMAC authentication.
IMPORTANT: do not use the default value, instead generate your own random
key.
This value must match the value specified in
Sitecore.PathAnalyzer.Services.RemoteServer.config.
-->
<setting name="PathAnalyzer.Remote.Authentication.ApiKey"
value="`%L$2I4quWUZULm^Y6%|R2dQP\vM';B5bT2H0|z\G\q8" />

<!-- PATH ANALYZER - REMOTE SERVICES - AUTHENTICATION - AUTHORIZED CLIENT ID
Specifies the unique application Id to use for HMAC authentication. This
value should be unique to Path Analyzer.
IMPORTANT: do not use the default value, instead generate your own random
value.
This value must be contained in the
"/sitecore/pathAnalyzer/remoteServices/configuration/authorizedClients" list specified in
Sitecore.PathAnalyzer.Services.RemoteServer.config.
-->
<setting name="PathAnalyzer.Remote.Authentication.AuthorizedClientId"
value="c241da4e6249fe8cd384384belca4865bff" />
```

2. In the `<pathAnalyzer>` section, replace the `<treeProvider>` element with the following one:

```
<treeProvider patch:instead="treeProvider"
type="Sitecore.PathAnalyzer.Data.Remote.RemoteTreeProvider, Sitecore.PathAnalyzer"
singleInstance="true" />
```

3. In the `<pathAnalyzer>` section, add the following element after the `<treeProvider>` element:

```
<!-- WEB REQUEST FACTORY
```

# Configuration File Changes

```
        This service is used to create secure web requests for communicating with
remote Path Analyzer services.
-->
    <webRequestFactory
type="Sitecore.PathAnalyzer.Data.Remote.RemoteWebRequestFactory, Sitecore.PathAnalyzer">
    <param desc="configuration" ref="pathAnalyzer/configuration" />
    <param desc="httpTransportFactory" ref="httpTransportFactory" />
    </webRequestFactory>
```

4. In the `<pathAnalyzer>` section, replace the `<remote>` element with the following one:

```
    <remoteServices>
    <!-- ENDPOINTS
        Defines endpoints that are used for communicating with services on the
remote reporting server.
-->
    <endpoints>

<treeDefinitionService>/sitecore/api/PathAnalyzer/RemoteTreeDefinition</treeDefinitionService>
    <treeService>/sitecore/api/PathAnalyzer/RemoteTree</treeService>
    <adminService>/sitecore/api/PathAnalyzer/RemoteAdmin</adminService>
    </endpoints>
    </remoteServices>
```

## 1.1.7 Changes to App\_Config\Include\Sitecore.PathAnalyzer.Services.RemoteServer.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.PathAnalyzer.Services.RemoteServer.config` file:

### Note

Apply the following changes only if the

`App_Config\Include\Sitecore.PathAnalyzer.Services.RemoteServer.config.disabled` file is enabled on your instance.

1. In the `<sitecore>` section after the `<settings>` element, add the following element:

```
    <!-- PATH ANALYZER -->
    <pathAnalyzer>
    <remoteServices>
    <!-- AUTHORIZED CLIENTS
        Specifies a list of client apps that are allowed to
communicate/authenticate with the services API.
        Apps must use their specified ID and API Key to successfully
authenticate via HMAC.
        IMPORTANT: do not use the default ID and key. You should generate your
own and ensure the client is configured to use the values you generate.
-->
    <configuration
type="Sitecore.PathAnalyzer.Services.Configuration.RemoteServicesConfiguration,
Sitecore.PathAnalyzer.Services">
    <authorizedClients hint="raw:AddClient">
    <client desc="PA_RemoteClient" id="c241da4e6249fe8cd384be1ca4865bff"
apiKey="%L$2I4quWUZULm^Y6%|R2dQP\vM';B5bT2H0|z\G\q8" />
    </authorizedClients>
    </configuration>
    </remoteServices>
    </pathAnalyzer>
```

2. In the `<sitecore>` section after the `<pathAnalyzer>` element, add the following element:

```
    <!-- PIPELINES -->
    <pipelines>
    <initialize>
    <processor
type="Sitecore.PathAnalyzer.Services.Pipelines.Initialize.RegisterRemoteFilters,
Sitecore.PathAnalyzer.Services" patch:after="processor[@type =
'Sitecore.PathAnalyzer.Services.Pipelines.Initialize.RegisterFilters,
Sitecore.PathAnalyzer.Services']" />
    </initialize>
    </pipelines>
```

# Sitecore Experience Platform 8.0 Update-1

3. In the `<api>/<services>` section, replace the `<configuration>` element with the following one:

```
<configuration
type="Sitecore.Services.Infrastructure.Configuration.ServicesConfiguration,
Sitecore.Services.Infrastructure">
  <allowedControllers hint="list:AddController">
    <allowedController
desc="PA_RemoteTreeController">Sitecore.PathAnalyzer.Services.Controllers.RemoteTreeController
, Sitecore.PathAnalyzer.Services</allowedController>
    <allowedController
desc="PA_RemoteTreeDefinitionController">Sitecore.PathAnalyzer.Services.Controllers.RemoteTree
DefinitionController, Sitecore.PathAnalyzer.Services</allowedController>
    <allowedController
desc="PA_RemoteAdminController">Sitecore.PathAnalyzer.Services.Controllers.RemoteAdminControll
er, Sitecore.PathAnalyzer.Services</allowedController>
  </allowedControllers>
</configuration>
```

4. Add the following controller to the end of the `<controllers>` section:

```
<!-- REMOTE ADMIN CONTROLLER
A Web API controller with actions used by the
/sitecore/admin/PathAnalyzer.aspx page
-->
<controller
type="Sitecore.PathAnalyzer.Services.Controllers.RemoteAdminController,
Sitecore.PathAnalyzer.Services">
  <param desc="propertyStore" ref="pathAnalyzer/propertyStore" />
  <param desc="configuration" ref="pathAnalyzer/configuration" />
</controller>
```

## 1.1.8 Changes to App\_Config\Include\Sitecore.Speak.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.Speak.config` file:

1. In the `<settings>` section, remove the following setting:

```
<!-- SPEAK COMPONENT COMPONENT PRESENTER
The name of the Component Presenter.
Default: scComponentPresenter
-->
<setting name="Speak.Components.KnockoutPresenter"
value="scComponentPresenter"/>
```

2. In the `<settings>` section, remove the following setting:

```
<!-- SPEAK HTML FRAME OPTIONS
Specifies the value of the X-Frame-Options HTTP header to be set in
response.
Default: SAMEORIGIN
-->
<setting name="Speak.Html.FrameOptions" value="SAMEORIGIN"/>
```

3. Remove the following processor from the `<speak.client.initialize.layout>` pipeline:

```
<processor type="Sitecore.Web.Pipelines.InitializeSpeakLayout.SetIframePolicy,
Sitecore.Speak.Client" />
```

## 1.1.9 Changes to App\_Config\Include\SwitchMasterToWeb.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `SwitchMasterToWeb.config` file:

### Note

Apply the following changes only if the `App_Config\Include\SwitchMasterToWeb.config.example` file is enabled on your instance.

- In the `<scheduling>` section, remove the following code:

# Configuration File Changes

```
<agent type="Sitecore.Tasks.DatabaseAgent">
  <patch:delete />
</agent>
<agent type="Sitecore.Tasks.DatabaseAgent">
  <patch:delete />
</agent>
<agent type="Sitecore.Tasks.DatabaseAgent" method="Run" interval="00:10:00">
  <param desc="database">core</param>
  <param desc="schedule root">/sitecore/system/tasks/schedules</param>
  <LogActivity>true</LogActivity>
</agent>
```

## 1.1.10 Changes to App\_Config\Include\ContentTesting\Sitecore.ContentTesting.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.ContentTesting.config` file:

1. Add the following event to the end of the `<events>` section:

```
<event name="item:saved:remote">
  <handler type="Sitecore.ContentTesting.Events.GenerateScreenshot,
Sitecore.ContentTesting" method="OnRemoteItemSaved">
    <excludeFields hint="list:ExcludeFieldFromComparison">
      <created>__created</created>
      <createdby>__created by</createdby>
      <updated> updated</updated>
      <updatedby> updated by</updatedby>
      <revision> revision</revision>
      <sortorder>__sortorder</sortorder>
      <validfrom>__valid from</validfrom>
      <workflow>__workflow</workflow>
      <workflowstate> workflow state</workflowstate>
      <lock> lock</lock>
      <pageleveltestsetdefinition> Page Level Test Set
Definition</pageleveltestsetdefinition>
    </excludeFields>
  </handler>
</event>
```

2. In the `<pipelines>` section after the `<getTestObjectives>` pipeline, add the following pipeline:

```
<!-- SESSIOND END
      Performs cleanup on session end
-->
<sessionEnd>
  <processor
type="Sitecore.ContentTesting.Pipelines.SessionEnd.CleanupPreservedWorkflowArgs,
Sitecore.ContentTesting"/>
  </sessionEnd>
```

## 1.1.11 Changes to App\_Config\Include\FXM\Sitecore.FXM.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.FXM.config` file:

- In the `<api>/<services>/<configuration>` section, remove the following allowed controller from `<allowedControllers>`:

```
<allowedController
desc="ExternalSiteProxyController">Sitecore.FXM.Service.Controllers.ExternalSiteProxyControlle
r, Sitecore.FXM.Service</allowedController>
```

## 1.1.12 Changes to App\_Config\Include\FXM\Sitecore.FXM.Lucene.Index.DomainsSearch.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.FXM.Lucene.Index.DomainsSearch.config` file:

1. In the `<contentSearch>` section, add the following element:

```
<indexConfigurations>
  <defaultFxmLuceneIndexConfiguration
type="Sitecore.ContentSearch.LuceneProvider.LuceneIndexConfiguration,
Sitecore.ContentSearch.LuceneProvider">

    <indexAllFields>false</indexAllFields>
    <initializeOnAdd>true</initializeOnAdd>

    <include hint="list:IncludeTemplate">
      <domainMatcherTemplateId>{036DB470-1850-4848-A48A-
0931F825B867}</domainMatcherTemplateId>
    </include>

    <include hint="list:IncludeField">
      <fieldId>{B5E02AD9-D56F-4C41-A065-A133DB87BDEB}</fieldId>
      <!-- display name -->
    </include>

    <fieldMap type="Sitecore.ContentSearch.FieldMap, Sitecore.ContentSearch">
      <fieldNames hint="raw:AddFieldByFieldName">

        <field fieldName="uniqueid" storageType="YES" indexType="TOKENIZED"
vectorType="NO" boost="1f" type="System.String"
settingType="Sitecore.ContentSearch.LuceneProvider.LuceneSearchFieldConfiguration,
Sitecore.ContentSearch.LuceneProvider">
          <analyzer
type="Sitecore.ContentSearch.LuceneProvider.Analyzers.LowerCaseKeywordAnalyzer,
Sitecore.ContentSearch.LuceneProvider" />
        </field>

        <field fieldName="_database" storageType="YES" indexType="TOKENIZED"
vectorType="NO" boost="1f" type="System.String"
settingType="Sitecore.ContentSearch.LuceneProvider.LuceneSearchFieldConfiguration,
Sitecore.ContentSearch.LuceneProvider">
          <analyzer
type="Sitecore.ContentSearch.LuceneProvider.Analyzers.LowerCaseKeywordAnalyzer,
Sitecore.ContentSearch.LuceneProvider" />
        </field>

        <field fieldName="urllink" storageType="YES" indexType="TOKENIZED"
vectorType="NO" boost="1f" type="System.String"
settingType="Sitecore.ContentSearch.LuceneProvider.LuceneSearchFieldConfiguration,
Sitecore.ContentSearch.LuceneProvider">
          <analyzer
type="Sitecore.ContentSearch.LuceneProvider.Analyzers.LowerCaseKeywordAnalyzer,
Sitecore.ContentSearch.LuceneProvider" />
        </field>

        <field fieldName="createdby" storageType="YES" indexType="TOKENIZED"
vectorType="NO" boost="1f" type="System.String"
settingType="Sitecore.ContentSearch.LuceneProvider.LuceneSearchFieldConfiguration,
Sitecore.ContentSearch.LuceneProvider">
          <analyzer
type="Sitecore.ContentSearch.LuceneProvider.Analyzers.LowerCaseKeywordAnalyzer,
Sitecore.ContentSearch.LuceneProvider" />
        </field>

        <field fieldName="updatedby" storageType="YES" indexType="TOKENIZED"
vectorType="NO" boost="1f" type="System.String"
settingType="Sitecore.ContentSearch.LuceneProvider.LuceneSearchFieldConfiguration,
Sitecore.ContentSearch.LuceneProvider">
          <analyzer
type="Sitecore.ContentSearch.LuceneProvider.Analyzers.LowerCaseKeywordAnalyzer,
Sitecore.ContentSearch.LuceneProvider" />
        </field>
      </fieldNames>
    </fieldMap>
  </defaultFxmLuceneIndexConfiguration>
</indexConfigurations>
```



# Configuration File Changes

```
        <field fieldName="revision" storageType="YES" indexType="TOKENIZED"
vectorType="NO" boost="1f" type="System.String"
settingType="Sitecore.ContentSearch.LuceneProvider.LuceneSearchFieldConfiguration,
Sitecore.ContentSearch.LuceneProvider">
        <analyzer
type="Sitecore.ContentSearch.LuceneProvider.Analyzers.LowerCaseKeywordAnalyzer,
Sitecore.ContentSearch.LuceneProvider" />
        </field>

        <field fieldName="domainmatchrule" storageType="YES"
indexType="TOKENIZED" vectorType="NO" boost="1f" type="System.String"
settingType="Sitecore.ContentSearch.LuceneProvider.LuceneSearchFieldConfiguration,
Sitecore.ContentSearch.LuceneProvider">
        <analyzer
type="Sitecore.ContentSearch.LuceneProvider.Analyzers.LowerCaseKeywordAnalyzer,
Sitecore.ContentSearch.LuceneProvider" />
        </field>
    </fieldNames>
</fieldMap>

<fields hint="raw:AddComputedIndexField">
    <field
fieldName="urllink">Sitecore.ContentSearch.ComputedFields.UrlLink, Sitecore.ContentSearch</field>
    <field
fieldName="createdby">Sitecore.FXM.Service.Data.DomainMatchers.ContentSearch.ComputedFields.CreatedBy, Sitecore.FXM.Service</field>
    <field
fieldName="updatedby">Sitecore.FXM.Service.Data.DomainMatchers.ContentSearch.ComputedFields.UpdatedBy, Sitecore.FXM.Service</field>
    <field
fieldName="revision">Sitecore.FXM.Service.Data.DomainMatchers.ContentSearch.ComputedFields.Revision, Sitecore.FXM.Service</field>
    <field
fieldName="domainmatchrule">Sitecore.FXM.Service.Data.DomainMatchers.ContentSearch.ComputedFields.DomainMatcherRule, Sitecore.FXM.Service</field>
</fields>

<!-- **** Inherited default configuration **** -->

    <analyzer
ref="contentSearch/indexConfigurations/defaultLuceneIndexConfiguration/analyzer" />
    <fieldReaders
ref="contentSearch/indexConfigurations/defaultLuceneIndexConfiguration/fieldReaders" />
    <indexFieldStorageValueFormatter
ref="contentSearch/indexConfigurations/defaultLuceneIndexConfiguration/indexFieldStorageValueFormatter" />
    <indexDocumentPropertyMapper
ref="contentSearch/indexConfigurations/defaultLuceneIndexConfiguration/indexDocumentPropertyMapper" />
    <documentBuilderType
ref="contentSearch/indexConfigurations/defaultLuceneIndexConfiguration/documentBuilderType" />

</defaultFxmLuceneIndexConfiguration>
</indexConfigurations>
```

2. In the <contentSearch>/<configuration>/<indexes> section, replace the <analytics\_fxm\_domains\_index\_master> index with the following one:

```
<index id="sitecore_fxm_master_index"
type="Sitecore.ContentSearch.LuceneProvider.LuceneIndex,
Sitecore.ContentSearch.LuceneProvider">
    <param desc="name">$(id)</param>
    <param desc="folder">$(id)</param>

    <!-- This initializes index property store. Id has to be set to the index
id -->
    <param desc="propertyStore"
ref="contentSearch/indexConfigurations/databasePropertyStore" param1="$(id)" />

    <configuration
ref="contentSearch/indexConfigurations/defaultFxmLuceneIndexConfiguration" />

    <strategies hint="list:AddStrategy">
        <!-- NOTE: order of these is controls the execution order -->
```

```

        <strategy
ref="contentSearch/indexConfigurations/indexUpdateStrategies/syncMaster" />
        </strategies>

        <locations hint="list:AddCrawler">
            <crawler type="Sitecore.ContentSearch.SitecoreItemCrawler,
Sitecore.ContentSearch">
                <Database>master</Database>
                <Root>/sitecore/system/Marketing Control Panel/fxm/</Root>
            </crawler>
        </locations>

    </index>

```

3. In the `<contentSearch>/<configuration>/<indexes>` section, replace the `<analytics_fxm_domains_index_web>` index with the following one:

```

        <index id="sitecore fxm web index"
type="Sitecore.ContentSearch.LuceneProvider.LuceneIndex,
Sitecore.ContentSearch.LuceneProvider">
            <param desc="name">$(id)</param>
            <param desc="folder">$(id)</param>

            <!-- This initializes index property store. Id has to be set to the index
id -->
            <param desc="propertyStore"
ref="contentSearch/indexConfigurations/databasePropertyStore" param1="$(id)" />

            <configuration
ref="contentSearch/indexConfigurations/defaultFxmLuceneIndexConfiguration" />
            <strategies hint="list:AddStrategy">
                <!-- NOTE: order of these is controls the execution order -->
                <strategy
ref="contentSearch/indexConfigurations/indexUpdateStrategies/onPublishEndAsync" />
            </strategies>

            <locations hint="list:AddCrawler">
                <crawler type="Sitecore.ContentSearch.SitecoreItemCrawler,
Sitecore.ContentSearch">
                    <Database>web</Database>
                    <Root>/sitecore/system/Marketing Control Panel/fxm/</Root>
                </crawler>
            </locations>

    </index>

```

## 1.1.13 Changes to App\_Config\Include\FXM\Sitecore.FXM.Solr.Index.DomainsSearch.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.FXM.Solr.Index.DomainsSearch.config` file:

### Note

Apply the following changes only if the `App_Config\Include\FXM\Sitecore.FXM.Solr.Index.DomainsSearch.config.disabled` file is enabled on your instance.

1. In the `<contentSearch>` section, add the following element:

```

        <indexConfigurations>
            <defaultFxmSolrIndexConfiguration
type="Sitecore.ContentSearch.SolrProvider.SolrIndexConfiguration,
Sitecore.ContentSearch.SolrProvider">
                <indexAllFields>>false</indexAllFields>
                <include hint="list:IncludeTemplate">
                    <domainMatcherTemplateId>{036DB470-1850-4848-A48A-
0931F825B867}</domainMatcherTemplateId>
                </include>
                <include hint="list:IncludeField">
                    <!-- display name -->

```

# Configuration File Changes

```
        <fieldId>{B5E02AD9-D56F-4C41-A065-A133DB87BDEB}</fieldId>
    </include>
    <fieldMap
ref="contentSearch/indexConfigurations/defaultSolrIndexConfiguration/fieldMap">
        <fieldNames hint="raw:AddFieldByFieldName">
            <fieldType fieldName="createdby" returnType="string" />
            <fieldType fieldName="updatedby" returnType="string" />
            <fieldType fieldName="revision" returnType="string" />
            <fieldType fieldName="domainmatchrule" returnType="string" />
        </fieldNames>
    </fieldMap>
    <fields hint="raw:AddComputedIndexField">
        <field fieldName="createdby"
returnType="string">Sitecore.FXM.Service.Data.DomainMatchers.ContentSearch.ComputedFields.Crea
tedBy, Sitecore.FXM.Service</field>
        <field fieldName="updatedby"
returnType="string">Sitecore.FXM.Service.Data.DomainMatchers.ContentSearch.ComputedFields.Upda
tedBy, Sitecore.FXM.Service</field>
        <field fieldName="revision"
returnType="string">Sitecore.FXM.Service.Data.DomainMatchers.ContentSearch.ComputedFields.Revi
sion, Sitecore.FXM.Service</field>
        <field fieldName="domainmatchrule"
returnType="string">Sitecore.FXM.Service.Data.DomainMatchers.ContentSearch.ComputedFields.Doma
inMatcherRule, Sitecore.FXM.Service</field>
    </fields>

    <fieldReaders
ref="contentSearch/indexConfigurations/defaultSolrIndexConfiguration/fieldReaders" />
    <indexFieldStorageValueFormatter
ref="contentSearch/indexConfigurations/defaultSolrIndexConfiguration/indexFieldStorageValueFor
matter" />
    <indexDocumentPropertyMapper
ref="contentSearch/indexConfigurations/defaultSolrIndexConfiguration/indexDocumentPropertyMapp
er" />
    <documentBuilderType
ref="contentSearch/indexConfigurations/defaultSolrIndexConfiguration/documentBuilderType" />

</defaultFxmSolrIndexConfiguration>
</indexConfigurations>
```

2. In the <contentSearch> section, replace the <configuration> sections for the <analytics\_fxm\_domains\_index\_master> and <analytics\_fxm\_domains\_index\_web> indexes with the single one:

```
    <configuration type="Sitecore.ContentSearch.ContentSearchConfiguration,
Sitecore.ContentSearch">
        <indexes hint="list:AddIndex">
            <index id="sitecore_fxm_master_index"
type="Sitecore.ContentSearch.SolrProvider.SolrSearchIndex,
Sitecore.ContentSearch.SolrProvider">
                <param desc="name">$(id)</param>
                <param desc="core">$(id)</param>
                <param desc="propertyStore"
ref="contentSearch/indexConfigurations/databasePropertyStore" param1="$(id)" />
            <configuration
ref="contentSearch/indexConfigurations/defaultFxmSolrIndexConfiguration" />
            <strategies hint="list:AddStrategy">
                <strategy
ref="contentSearch/indexConfigurations/indexUpdateStrategies/syncMaster" />
            </strategies>
            <locations hint="list:AddCrawler">
                <crawler type="Sitecore.ContentSearch.SitecoreItemCrawler,
Sitecore.ContentSearch">
                    <Database>master</Database>
                    <Root>/sitecore/system/Marketing Control Panel/fxm/</Root>
                </crawler>
            </locations>
        </index>
        <index id="sitecore_fxm_web_index"
type="Sitecore.ContentSearch.SolrProvider.SolrSearchIndex,
Sitecore.ContentSearch.SolrProvider">
            <param desc="name">$(id)</param>
            <param desc="core">$(id)</param>
            <param desc="propertyStore"
ref="contentSearch/indexConfigurations/databasePropertyStore" param1="$(id)" />
```

```
<configuration
ref="contentSearch/indexConfigurations/defaultFxmSolrIndexConfiguration" />
  <strategies hint="list:AddStrategy">
    <strategy
ref="contentSearch/indexConfigurations/indexUpdateStrategies/onPublishEndAsync" />
    </strategies>
  <locations hint="list:AddCrawler">
    <crawler type="Sitecore.ContentSearch.SitecoreItemCrawler,
Sitecore.ContentSearch">
      <Database>web</Database>
      <Root>/sitecore/system/Marketing Control Panel/fxm</Root>
    </crawler>
  </locations>
</index>
</indexes>
</configuration>
```

## 1.1.14 Changes to App\_Config\Include\ListManager\Sitecore.ListManagement.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.ListManagement.config` file:

1. In the `<listManagement.associateContacts>` pipeline, replace the `<processor type="Sitecore.ListManagement.ContentSearch.Pipelines.AssociateContact.AssociateContacts, ...</processor>` processor with the following one:

```
<processor
type="Sitecore.ListManagement.ContentSearch.Pipelines.AssociateContact.AssociateContacts,
Sitecore.ListManagement.ContentSearch">
  <ContactProcessingProvider ref="processContactsDataProvider" />
</processor>
```

2. In the `<listManagement.importMediaContacts>` pipeline, replace the `<processor type="Sitecore.ListManagement.ContentSearch.Pipelines.ImportMediaContacts.ImportContacts, ...</processor>` processor with the following one:

```
<processor
type="Sitecore.ListManagement.ContentSearch.Pipelines.ImportMediaContacts.ImportContacts,
Sitecore.ListManagement.ContentSearch">
  <ContactProcessingProvider ref="processContactsDataProvider" />
</processor>
```

3. In the `<listManagement.removeContactAssociations>` pipeline, replace the `<processor type="Sitecore.ListManagement.ContentSearch.Pipelines.RemoveContactAssociations.RemoveAssociationsFromIndex, ...</processor>` processor with the following one:

```
<processor
type="Sitecore.ListManagement.ContentSearch.Pipelines.RemoveContactAssociations.RemoveAssociationsFromIndex,
Sitecore.ListManagement.ContentSearch">
  <ContactProcessingProvider ref="processContactsDataProvider" />
</processor>
```

## 1.1.15 Changes to App\_Config\Include\Social\Sitecore.Social.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.Social.config` file:

- In the `<commands>` section, remove the following command:

```
<command name="social:links:rundashboard"
type="Sitecore.Social.Client.Commands.RunDashboard, Sitecore.Social.Client" />
```

# Configuration File Changes

## 1.1.16 Changes to App\_Config\Include\XdbCloud\Sitecore.Cloud.Xdb.config

To upgrade your existing config file to the Sitecore 8.0 rev. 150121 (Update-1) version, you must make the following changes to the `Sitecore.Cloud.Xdb.config` file:

### Note

Apply the following changes only if the

`App_Config\Include\XdbCloud\Sitecore.Cloud.Xdb.config.disabled` file is enabled on your instance.

1. In the `<pipelines>` section, remove the `ExperienceProfileAggregateViews` group.
2. In the `<sitecore>` section, remove the `<experienceProfile>` element.